




































# Lyall Meter Sets, Steel Pipe, Pre-bent/Welded Configuration Guide

## Component Configuration



















Inlet Style	Inlet Orientation	Inlet Thread	Swivel Size	Swivel Spacing	Outlet Style	Outlet Orientation	Outlet Thread	Coating Type
 <input type="checkbox"/> 180° Bend	 <input type="checkbox"/> Side	 <input type="checkbox"/> Male Thread   <input type="checkbox"/> Female Thread	<input type="checkbox"/> #1 Spge <input type="checkbox"/> 1" Pitts <input type="checkbox"/> 10 Lite <input type="checkbox"/> 20 Lite <input type="checkbox"/> 30 Lite <input type="checkbox"/> 45 Lite <input type="checkbox"/> 60 Lite <input type="checkbox"/> Thrded	<input type="checkbox"/> 6" <input type="checkbox"/> 7" <input type="checkbox"/> 8¼" <input type="checkbox"/> 8½" <input type="checkbox"/> 11"	 <input type="checkbox"/> 180° Bend	 <input type="checkbox"/> Side   <input type="checkbox"/> 90° Back	 <input type="checkbox"/> Male Thread   <input type="checkbox"/> Female Thread	<input type="checkbox"/> Polyester <input type="checkbox"/> Zinc Only <input type="checkbox"/> Polyester Over Zinc <input type="checkbox"/> Black
 <input type="checkbox"/> 90° Bend	 <input type="checkbox"/> 90° Back	<b>Inlet Size</b> <input type="checkbox"/> ¾" <input type="checkbox"/> 1" <input type="checkbox"/> 1¼" <input type="checkbox"/> 1½"			 <input type="checkbox"/> 90° Bend	 <input type="checkbox"/> 90° Back	<b>Outlet Size</b> <input type="checkbox"/> ¾" <input type="checkbox"/> 1" <input type="checkbox"/> 1¼" <input type="checkbox"/> 1½"	
 <input type="checkbox"/> Double Bend	 <input type="checkbox"/> 45° Back					 <input type="checkbox"/> Double Bend	 <input type="checkbox"/> 45° Back	
 <input type="checkbox"/> Straight	 <input type="checkbox"/> Top				 <input type="checkbox"/> Straight	 <input type="checkbox"/> Top		

## Component Options

Inlet Type	Outlet Type	Bypass Type/Tap	Bypass Tap Plug	Comments / Notes
<b>Union</b>  <input type="checkbox"/> Insulated  <input type="checkbox"/> Non-Insulated	<b>Union</b>  <input type="checkbox"/> Insulated  <input type="checkbox"/> Non-Insulated	<b>LycoSaver</b>  Tap Facing <input type="checkbox"/> Front <input type="checkbox"/> Side <input type="checkbox"/> Rear	 <input type="checkbox"/> Hole   <input type="checkbox"/> No Hole	<input type="checkbox"/> A9 Valve w/bypass  <input type="checkbox"/> Grunsky  <input type="checkbox"/> A9 Back <input type="checkbox"/> A9 Side <input type="checkbox"/> Gsky Back <input type="checkbox"/> Gsky Side
<b>Shutoff Valve</b>  <input type="checkbox"/> Insulated  <input type="checkbox"/> Non-Insulated	<b>Shutoff Valve</b>  <input type="checkbox"/> Insulated  <input type="checkbox"/> Non-Insulated	<b>¼" Tap</b>  Tap Facing <input type="checkbox"/> Front <input type="checkbox"/> Side <input type="checkbox"/> Rear		
<b>Union/Valve Type</b> <input type="checkbox"/> Standard <input type="checkbox"/> Short	<b>Union/Valve Type</b> <input type="checkbox"/> Standard <input type="checkbox"/> Short			

- Some swivel sizes are limited to specific pipe size.
- Meter bars with A9 Bypass valves can only have zinc or polyester over zinc coating.
- LycoSaver Bypass Valves can only be installed in configurations using 1 IPS steel tubing outlet sizes.
- Please contact your Lyall representative for special requirements.

# Standard Inlet / Outlet Styles

 <p>A</p>	 <p>B</p>	 <p>C</p>
 <p>D</p>	 <p>E</p>	 <p>F</p>
 <p>G</p>	 <p>H</p>	 <p>J</p>
 <p>K</p>	 <p>L</p>	 <p>M</p>
 <p>N</p>	 <p>P</p>	 <p>R</p>
 <p>S</p>	 <p>Side      90° Back      45° Back      Top</p> <p>Standard Inlet Orientation</p>	
 <p>Side      90° Back      45° Back      Top</p> <p>Standard Outlet Orientation</p>		